

Advertising Digital Delivery

Advertising material delivered digitally to Fairfax Media Publications will only be accepted if the file includes the correct Fairfax booking identification number.

Fairfax Advertising Production Support

Complete advertising material for Fairfax Media Publications must be saved as a PDF and delivered via one of the approved delivery channels listed below. For advice regarding these services, please contact them directly on the numbers shown.

Phone: +61 1300 666 326
Email: www.fairfax.com.au/specs

AdDesigns

AdDesigns is a one stop design solution specialising in meeting customer needs in all Fairfax Media Publications.

Level 2, 33 Moore Street, Liverpool NSW 2170
Phone: +61 2 8777 6956
Fax: +61 2 8777 6693
Email: addesigns@fairfaxmedia.com.au

AdOnline

AdOnline is the integrated Fairfax booking, delivery and tracking service available to high volume users (one or more ads booked & delivered per week). The website address is www.adonline.com.au

Phone: 1300 666 599

Adstream**

Adstream (formerly Quickcut) provides software to assist with PDF validation and can arrange delivery of your ad on a fee-for-service basis to most newspapers and magazines in Australia. More information is available at www.adstream.com

Sydney

Level 5, Tower B, 207 Pacific Highway, St. Leonards NSW 2065
Phone: +61 2 9467 7500
Toll Free: 1800 230 302
Fax: +61 2 9467 7602
Tech Support: 1300 768 988

Melbourne

Level 1,
15-29 Bank Street, South Melbourne VIC 3205
Phone: +61 3 8696 5701
Fax: +61 3 9696 4556

Brisbane

Cnr Riverside Drive and Jane Street, West End QLD 4101
Phone: +61 7 3013 6279
Fax: +61 7 3013 6298

Adelaide

64 North Terrace, Kent Town SA 5067
Phone: +61 8 8366 0914
Fax: +61 8 8366 0909
Email: anneb@adstream.com

WebSEND**

WebSEND is a digital delivery service that will validate PDF files and arrange immediate delivery of ads to most newspapers and magazines in Australia. For more information visit www.websend.com.au


Level 18, 31 Queen Street VIC 3000
Phone: +61 3 8689 9000
Fax: +61 3 9614 5344

Size Specifications


Television Sizes

Please note Ad size dimensions are height by width

Pages




Code
Size (mm) **Full Page**
320x252




Code
Size (mm) **Double Page Spread**
320x522


Horizontals



Code
Size (mm) **Half Page**
155x252



Code
Size (mm) **Quarter Page**
90x252



Code
Size (mm) **Front Page Strip**
58x252

Sizing

General

When preparing your advertisement in your native program, please ensure that your paper size and your advertisement size are the same. Bleed and registration marks are not required.

Preparing Artwork

The specifications below are provided to assist with the preparation and creation of PDF files for advertising use

Newsprint Publications

General

| | | | |
|------------------|-----|---------------|-----------|
| PDF version | 1.3 | ICC compliant | No |
| PostScript level | 3 | Colour model | CMYK only |

Fonts & Type

Type that has been set outside the recommendations shown is likely to reproduce poorly. Fairfax will not accept any claim for compensation for poor type reproduction where these recommendations have not been met. Ads with type set outside Fairfax recommendations are accepted and run entirely at the advertisers risk.

| | |
|---|------|
| Font embedding required | Yes |
| Font subsetting allowed | Yes |
| Recommended point size for coloured type | 8pt |
| Recommended weight for coloured type | Bold |
| Recommended plates allowed for coloured type | 3 |
| Recommended point size for reversed type | 12pt |
| Recommended weight for reversed type | Bold |
| Recommended plates allowed for reversed type | 3 |
| Recommended point size for single colour type (100% C,M,Y or K) | 6pt |

Images

| | | | |
|--|-------------|---|-------------|
| Format | EPS, TIFF | Dot aim point (C,M,Y,K) for essential whites | 3%,2%,2%,0% |
| Minimum resolution for colour images | 200dpi | Dot aim point (Colour) for midtones | 30% |
| Minimum resolution for greyscale images | 200dpi | Dot aim point (Colour) for shadow (max) | 240% |
| Minimum resolution for black & white (single bit) images | 600dpi | Dot aim point for shadow (black max) | 80% |
| Total ink weight | 240% | Dot aim point (Mono) for Catchlights | 0% |
| Dot aim point (C,M,Y,K) for Catchlights | 0%,0%,0%,0% | Dot aim point (Mono) for non essential whites | 0% |
| Dot aim point (C,M,Y,K) for Highlights | 0%,0%,0%,0% | Dot aim point (Mono) for midtones | 30% |
| Dot aim point (C,M,Y,K) for non essential whites | 0%,0%,0%,0% | Dot aim point for shadow (max) | 92% |

Auto Ink Weight Management

Fairfax Media has state of the art ink weight adjustment software in place, any material supplied with ink weight exceeding the specified 240% limit will be automatically adjusted.

Please consult Technical Reproduction Guidelines for each newspaper before submitting any artwork.

Vector art (logos)

| | |
|------------------|-----------|
| Format | EPS |
| PostScript level | 3 |
| Colour model | CMYK only |

Logos

All logos should be supplied as either single bitmap or vector artwork.

Digital advertisements

Submitted to Fairfax must be saved as Portable Document Format (PDF).

Please note that PDF files must be created with a PostScript application.

We accept press ready, high resolution PDF files. We recommend saving the file as an EPS out of your native program and using Acrobat Distiller to create the PDF. PDF's generated from native programs such as InDesign, Quark Express, Illustrator or Freehand are acceptable.

Fully rasterised pdfs from or placed in any application are not acceptable, due to extremely poor reproduction of fonts.

The following applications are not PostScript compatible and are not suitable for creating PDFs for Fairfax:

Microsoft Word
 Microsoft Excel
 Microsoft PowerPoint
 Microsoft Publisher
 Adobe PhotoShop

Further details over the page.

Preparing Artwork

The specification below is provided to assist with the preparation and creation of PDF files for advertising use.

Newsprint Publications *continued*

Instructions for creating PDF files

The preferred method for creating a PDF file is shown below.

Step 1

Create an EPS file using a PostScript software application.

Instructions for popular PostScript applications can be found here:

Freehand v9 – v10

InDesign v1 – v2

PageMaker v7 (Mac)

PageMaker v7 (Windows)

Illustrator v8 – v10

PageMaker v6 – v6.5

QuarkXPress v4

Step 2

Convert the EPS to PDF using Adobe Acrobat Distiller.

Job Options for Distiller can be downloaded here:

To download Windows Job Options, right-click on the link and select “Save target as”.

To download Mac Job Options, Control-click on the link and select “Download link to disk”.

| | | |
|-------------------|----------------|----------------|
| Newspapers | Acrobat | Mac Windows |
| Magazines | Acrobat | Mac Windows |

Photoshop Colour Settings File

A Colour Settings File (CSF) has been developed to use Photoshop to enable effective image conversion from RGB to CMYK or RGB to Greyscale.

In converting the image this file will also adjust maximum ink weight and incorporate Grey Component Replacement (GCR) settings for newsprint.

The Photoshop CSF file with newsprint settings can be downloaded here:

| CSF type | Example | Platform |
|---------------------------|---------------------------|-----------------------------|
| Fairfax newsprints | the Age | CSF (<i>readme files</i>) |
| | the Sydney Morning Herald | CSF (<i>readme files</i>) |
| | the Sun-Herald | ICC (<i>readme files</i>) |
| | the Financial Review | ICC (<i>readme files</i>) |

Technical Reproduction Guidelines

Fairfax advertising material both colour and mono must be sent electronically.

Screen Rulings

- 4 Colour and Mono Digital artwork files should be set for screen ruling of 110LPI / 40LPC

Material Requirements / Production Guidelines

For Digital copy:

Colour Models:

Spot Colour

1. Spot colours must be modified to separate in CMYK.
- This is achieved using the four colour printing process by combining varying percentages of process colours, comprising the CMYK (cyan, magenta, yellow and black).
 - PMS colour values must not be used.
 - When producing spot colour mechanically with process colour inks, it is important to take dot gain and secondary colour contamination into consideration.

Dot Aim Points - Colour

- Images should allow for a dot gain of up to 30% in the mid-tone area. Ensure mid-tones are lighter and have more contrast for newsprint reproduction to compensate for the above dot gain. The mid to three-quarter tones have to be adjusted as newsprint tends to flatten these areas.

Process Colour

2. Every colour specified in every application used must be defined using the CMYK colour model.
- Process Colour is specified in percentages of CMYK-the primary colours (Cyan, Magenta, Yellow and Black). Four-colour process is achieved by over printing different proportions of two or more of the primary colours to produce a wide range of colours and tones.
 - **Screen ruling: 110LPI / 40LPC**
 - **Dot Structure: Round.**
 - **Screen angles: Cyan 15°, Magenta 75°, Yellow 90°, Black 45°**
 - **Print sequence: Cyan, Magenta, Yellow, Black.**

| | C | M | Y | K |
|-------------------|----|----|----|----|
| Catchlights | 0% | 0% | 0% | 0% |
| Highlights | 0% | 0% | 0% | 0% |
| Non detail whites | 0% | 0% | 0% | 0% |
| Essential whites | 3% | 2% | 2% | 0% |
| Midtones | | | | |
| Shadow | | | | |

Allow up to 30% dot gain
not to exceed 230%, limit black to 80%

Colour Tonal Reproduction Guidelines

Grey Component Replacement (GCR)

When separating material for newspaper reproduction Fairfax recommends the use of GCR.

- Grey component Replacement (GCR) is a procedure used in the colour separation process. GCR uses the black printer to replace cyan, magenta and yellow, not only in the neutral areas throughout the tonal range, but also in the colours of the separation.
- The application of GCR improves the shadow detail, helps compensate for dot gain and reduces the ink weight carried, thus reducing ink set-off and show-through. This function helps produce more stable greys/ neutrals and minimises colour shifts due to slight ink variances on press. Ink trapping within the separation also improves.

The following are the reasons Fairfax specifications require the scanner operator to apply GCR.

- Figures supplied serve as general guidelines only. It will be up to the trade house or scanner operator to assess each image and subject individually, and apply the suitable range of GCR.
- Depending on the original, for better printing quality, a GCR value of 80% is suggested for use in separations for maximum results. Any higher than this benchmark could result in a coarse (grainy) result.
- Many GCR programs use full-range application, which places black in the highlight and quartertones. However, if the resulting black dot is too large, colours and flesh tones will become grey and dirty on the press.
- Most line illustrations with wash colours or pictures containing pastel colour should not have GCR applied and will reproduce better if conventional UCR (under colour removal) techniques are used.

In addition to the issues addressed in "Tonal reproduction guidelines", the following are strategies which, from a technical standpoint, further determine the success of the process colour image separations and their final reproduction.

Grey Balance

- Maintaining grey balance throughout the separation is extremely important for quality four-colour reproduction.
- Separations without neutral greys will reproduce with perceivable colour casts on press. As a general rule for newsprint reproduction, grey balance requires slightly more cyan relative to less amounts of magenta to yellow, (E.g. 32 cyan, 20 magenta, 24 yellow).

Colour Correction

- In addition to addressing colour casts in an original, colour correction takes on greater meaning in complementing the inks and the stock used. Colour correction should be utilised in all colour separations generated for newsprint reproduction.
- The main purpose of colour correction is to reduce the underlying colours, which tend to dirty the colours on newsprint stock. Significant improvement in reproduction quality can be obtained by keeping images clean and bright through minimising contaminated colours. For example, taking yellow out of blues, magenta out of greens, cyan out of yellows and so on without sacrificing detail to obtain clean colours, which significantly increases the quality of the reproduction.

These colour techniques and recommendations will produce cleaner, brighter images and can be applied to any kind of creative without the need to sacrifice mood. Following these recommendations will provide the best opportunity of reproducing colour on press.

Technical Reproduction Guidelines

Mono Tonal Reproduction Guidelines

Non Essential White Drop Out

- Remove all printing dots from the non-essential whites to maximise the entire available print range between paper brightness and total ink saturation.

Dot Gain

- Allow for a 30% dot gain in the mid-tone range.

Contrast

- Allow at least 20% difference between adjoining tones to allow for the above dot gain. Exaggerate contrast, as newsprint will flatten the mid-tone areas so allowances must be made to this area.

Sharpness (U.S.M.)

- Sharpness should be a little exaggerated with a distinct tonal adjacency (break between the tones), as this will soften when reproduced on newsprint.

Midtones

- Original manipulation of mid-tones must be adjusted correctly, if not it will result in images printing too dark or flat, even though specifications have been adhered to.
- Mid-tone replacement is dependent on each image or subject content.
- Mid-tones should be lightened (less printing weight) for dark images.

Shadows

- A common error made in tone reproduction is to make necessary mid-tone adjustments without restoring the shadow range. Because the shadow is pulled open by the mid-tone adjustments, it is important to restore the shadow end to its maximum density. Shadows are black but no three-quarter detail should be missing.

Typeface Guidelines

Fairfax holds no responsibility for the printed reproduction of any typeface that does not fit the following specification.

Fonts

- Always use Postscript (or Postscript compatible) fonts.
- Fairfax recommends that no True Type fonts be used in any applications. True Type fonts can be identified by looking at the font properties in Adobe Type Manager, or file information on the Macintosh. They will be identified as True Type font rather than postscript font.
- CID / Unicode / Double Byte fonts are not supported.
- Although Fairfax supports all fonts in the Adobe Type family, version differences can cause problems.

Embedding Fonts

- All fonts must be embedded and subset when creating PDF files. (Fonts not embedded will revert to Courier default at the RIP).
- Go to - Downloads for Font embedding and step by step instructions.

Typefaces

Sans serif typefaces are the recommended choice for newsprint reproduction. They reproduce easily with the desired readability.

Production Tips When Using Typefaces in Colour

Coloured Type on white background

- The best Sans Serif typefaces to use in design of coloured type on white background should be bold and solid and have no fine line work in them.
- The recommended type size for (Coloured Type on White Background using single colours) is - **6pt**.
- The recommended type size for (Coloured Type on White Background using two or three colours) is - **8pt**.
- It is not recommended that typefaces print using four colours. If used it should be Sans Serif and bold the recommended type size is. - **12pt**.
- Type with fine serifs or are screened to make up a required colour should be **12pt** or greater in size. Smaller typefaces will create registration and legibility problems when printing.
- Final reproduction results should be considered when attempting to reproduce type as a light screen tint. For best results, avoid screening type styles with a fine to medium weight and those with serifs. Minimum type size for this application is. - **12pt**.
- Due to the relationship of ink, newsprint and the press, small type tends to lose definition when printed. Typefaces with thin or delicate serifs and strokes should be avoided. Extremely fine strokes can drop out, while thick strokes can plug in on the press.
- The recommended type size for (Reverse Type using one process colour) is - **8pt**.

It is not recommended to reverse type out of single colour yellow.

Overprint type

- When using solid coloured type overprinting a background tint, it is suggested that type not overprint a background screen (tint or ghosted image) greater than 30% visual density. This allows for dot gain and provides the necessary contrast between text matter and the background image.

Type size recommendations for overprint type: As above for coloured type on white background.

Reverse type out of coloured / solid or halftone panels

- When reversing type out of panels it is recommended that this be limited to using three colours only.
- For contrast and readability, reverse type should not be positioned within screened areas less than 50% or in yellow or light coloured backgrounds.
- Recommended text size of reversed type out of a four-colour image, type with fine serifs or type with screens, is **12pt and should be in bold face**. This allows for press variations in register while maximising legibility.
- The minimum thickness on all reversed type out of 2 or 3 colours should be at least 0.75 point thickness, it is not recommended to reverse serifed faces at all or out of 4 colours.

Technical Reproduction Guidelines

Colour Saturation Tip

- Coloured type or solid panels with reverse type can print using a single colour at 100%. When a second, third or fourth colour is required for colour makeup, these extra colours should be limited to 90%, keeping within the total ink limit of 240%. This will allow the ink to trap on the press and result in consistent and balanced printing.

Point Sizes

- The recommended text size for a SINGLE solid colour of (100% C, M, Y, K). **6pt.**
- The recommended type size for (Coloured type on white background using two or three colours). **8pt.**
- The recommended type size for (Coloured type on white background using four colours). **12pt.**
It is not recommended that typefaces print using four colours. If used should be Sans Serif and bold.
- The recommended type size for (Type with fine serifs). (Type screened to make up a required colour). **12pt.**
- The recommended type size for (Type as a light screen tint). **12pt.**
- The recommended type size for (Reversed type, out of a four-colour image). **12pt.**
(Reversed type, with fine serifs). (Reversed type, with screens).

Font Thickness

Typefaces reversed out of two or more colours should have a recommended thickness and be Sans Serif (see above Typeface points for what to avoid); again this will allow for press variation in register while maximising legibility.

Recommended text thickness or width reversed out of one or more colours 0.125mm (0.005 inch)- 1.5pt

Line Thickness

- Minimum width 0.125mm (0.005 inch) with a maximum of two colours overprinting.
- Avoid line art less than 1 pt.

File Format

Standardising on the following files formats when creating the material is essential to providing accurate output results.

Colour bitmap images

Colour bitmap images are generally 8 bit that are device dependent, these images should be saved at twice the line screen ruling of the publication to ensure proper reproduction while allowing for a safety margin.

Recommended effective resolution for Colour images: 150dpi.

Colour images should be saved in TIFF or EPS format, without compression, transfer or screen functions, alpha channels or any other colour profiles associated.

- Vector art. Vector is typically produced using Bezier curves and lines, using products such as Adobe Illustrator. As vector art is device independent, no minimum resolution is applicable.
- To avoid PostScript errors, most drawing packages can automatically split complex paths into smaller ones (i.e. split long paths) Fairfax recommends using this option.
 - The resolution standards recommended for Colour images as shown above should be adhered to when placing scanned images into vector art.

Vector art should be saved in EPS format.

Standard file formats for Mono

Single bit Images.

Single bit images are typically used for scanned line art. Although single bit images can be scanned up to the resolutions of the output devices being used no discernable difference has been found when using the Fairfax recommended settings.

Recommended effective resolution for single bit images: 1600dpi. Single bit images should be saved in TIFF format, without compression.

Grayscale bitmap images

Grayscale bitmap images are generally 8 bit that are device dependent, these images should be saved at twice the line screen ruling of the publication to ensure proper reproduction while allowing for a safety margin.

Recommended effective resolution for Grayscale images: 150dpi.

Grayscale images should be saved in TIFF or EPS format, without compression, transfer or screen functions, alpha channels or any other colour profiles associated.

Vector art

Vector is typically produced using Bezier curves and lines, using products such as Adobe Illustrator. As vector art is device independent, no minimum resolution is applicable.

- To avoid PostScript errors, most drawing packages can automatically split complex paths into smaller ones (i.e. split long paths) Fairfax recommends using this option.
- The resolution standards recommended for Single bit and Grayscale images as shown above should be adhered to when placing scanned images into vector art.

Vector art should be saved in EPS format.